



Embases acier massif

Ø 100 à 120

Embase acier
Tige acier
Pied articulé oscillant fixable



| CODE | | DÉSIGNATION | DIMENSIONS | | | | | | | | CHARGE MAXI | |
|-----------|--------------|-------------|------------|-----|-----|----|---|-----|----|-----|-------------|--------|
| Standard | avec semelle | | A | B | D | | M | G | H | H1 | Newton | |
| MA-15509 | MA-15509/G | M16x75 | 25 | 75 | 100 | 20 | ⬡ | M16 | 16 | 100 | 103 | 30 000 |
| MA-15510 | MA-15510/G | M16x100 | 25 | 100 | 100 | 20 | ⬡ | M16 | 16 | 125 | 128 | 30 000 |
| MA-15511 | MA-15511/G | M16x150 | 25 | 150 | 100 | 20 | ⬡ | M16 | 16 | 175 | 178 | 30 000 |
| MA-15512 | MA-15512/G | M20x75 | 25 | 75 | 100 | 20 | ⬡ | M20 | 16 | 100 | 103 | 30 000 |
| MA-15513 | MA-15513/G | M20x125 | 25 | 125 | 100 | 20 | ⬡ | M20 | 16 | 150 | 153 | 30 000 |
| MA-15514 | MA-15514/G | M20x175 | 25 | 175 | 100 | 20 | ⬡ | M20 | 16 | 200 | 203 | 30 000 |
| MA-15515 | MA-15515/G | M24x100 | 25 | 100 | 100 | 24 | ⬡ | M24 | 16 | 125 | 128 | 35 000 |
| MA-15516* | MA-15516/G* | M24x150 | 25 | 150 | 100 | 24 | ⬡ | M24 | 16 | 175 | 178 | 35 000 |
| MA-15517* | MA-15517/G* | M24x200 | 25 | 200 | 100 | 24 | ⬡ | M24 | 16 | 225 | 228 | 35 000 |
| MA-15518 | MA-15518/G | M30x125 | 26 | 125 | 100 | 30 | ⬡ | M30 | 16 | 151 | 154 | 35 000 |
| MA-15519* | MA-15519/G* | M30x175 | 26 | 175 | 100 | 30 | ⬡ | M30 | 16 | 201 | 204 | 35 000 |
| MA-15520* | MA-15520/G* | M30x225 | 26 | 225 | 100 | 30 | ⬡ | M30 | 16 | 251 | 254 | 35 000 |
| MA-15521 | MA-15521/G | M16x75 | 25 | 75 | 120 | 20 | ⬡ | M16 | 16 | 100 | 103 | 35 000 |
| MA-15522 | MA-15522/G | M16x100 | 25 | 100 | 120 | 20 | ⬡ | M16 | 16 | 125 | 128 | 35 000 |
| MA-15523 | MA-15523/G | M16x150 | 25 | 150 | 120 | 20 | ⬡ | M16 | 16 | 175 | 178 | 35 000 |
| MA-15524 | MA-15524/G | M20x75 | 25 | 75 | 120 | 20 | ⬡ | M20 | 16 | 100 | 103 | 40 000 |
| MA-15525 | MA-15525/G | M20x125 | 25 | 125 | 120 | 20 | ⬡ | M20 | 16 | 150 | 153 | 40 000 |
| MA-15526 | MA-15526/G | M20x175 | 25 | 175 | 120 | 20 | ⬡ | M20 | 16 | 200 | 203 | 40 000 |
| MA-15527 | MA-15527/G | M24x100 | 25 | 100 | 120 | 24 | ⬡ | M24 | 16 | 125 | 128 | 40 000 |
| MA-15528* | MA-15528/G* | M24x150 | 25 | 150 | 120 | 24 | ⬡ | M24 | 16 | 175 | 178 | 40 000 |
| MA-15529* | MA-15529/G* | M24x200 | 25 | 200 | 120 | 24 | ⬡ | M24 | 16 | 225 | 228 | 40 000 |
| MA-15530 | MA-15530/G | M30x125 | 26 | 125 | 120 | 30 | ⬡ | M30 | 16 | 151 | 154 | 40 000 |
| MA-15531* | MA-15531/G* | M30x175 | 26 | 175 | 120 | 30 | ⬡ | M30 | 16 | 201 | 204 | 40 000 |
| MA-15532* | MA-15532/G* | M30x225 | 26 | 225 | 120 | 30 | ⬡ | M30 | 16 | 251 | 254 | 40 000 |

* Référence disponible au pas fin (code + P2)

matière

Embase en acier zingué C40.
Tige en acier zingué livrée sans écrou.
Semelle en caoutchouc NBR dureté 70° shore H6 (80° sur demande).

note

Réalisation de dimensions et finitions spéciales de tiges filetées dès 150 pièces.

